

## 4 Camera H.264 120fps Triplex Embedded DVR with DVD-RW backup

**Model:** DVRH4



### Features

- 4 Channel Input
- Triplex (Recording, Playback, Network all at the s
- H.264 Compression
- Hybrid (supports IP cameras)
- Remote Viewing
- Real Time Display
- Up to 120fps Recording Speed
- Calendar Search
- Full Mouse Support
- Archiving via USB and DVD-RW
- Stable Operation System (Embedded Linux)
- Central Management System (CMS) software for l video management
- Firmware Upgradeable
- Scheduled Recording
- Password Protection
- Network Connection
- IE Web Server and Remote Client
- PTZ Control via RS-485 (Pelco D, Pelco P)
- Camera Installation Plug & Play
- Automatic Camera Detection
- Supports Covert Camera Operation
- Supports Pre-Alarm Recording
- USB 2.0 Port for Video Clip Exporting
- Built with ezBurn™, ezRecord™, ezDDNSTM Tec
- IR Remote Control Included
- Hard drive purchased separately

### Specifications

<b>Camera Inputs:</b>	4
<b>Image Compression:</b>	H.264 /MJPEG
<b>Operating System:</b>	Embedded Linux
<b>Operation:</b>	Triplex(Playback / Record / Network View)
<b>Video Input:</b>	BNC x 4, 1.0Vp-p, 75 ohm
<b>Video Output:</b>	BNC to main monitor
<b>Video Output:</b>	VGA 800 x 600, 1024 x 768, 1280 x 1024 pixels
<b>Audio Inputs:</b>	4
<b>Audio Outputs:</b>	2
<b>Hard Drive:</b>	purchased separately, 2 HD Maximum (up to 2 Terabyte)
<b>Display:</b>	30 fps per channel (@720 x 480)
<b>Recording Rate:</b>	120 fps (@352 x 240), 60 fps (@720 x 240), 30 fps (@720 x 480)

<b>Recording Qualities:</b>	8 Preset Levels
<b>Recording:</b>	Schedule, Alarm, Motion Detection
<b>Search:</b>	Time, Date, Event
<b>Playback Speeds:</b>	1X, 2X, ...32X
<b>Alarm Inputs:</b>	4 D-Sub
<b>Alarm Outputs:</b>	1 relay output D-Sub
<b>Pre-Alarm operation:</b>	Yes
<b>PTZ Control</b>	RS-485 interface
<b>Archiving</b>	USB 2.0, DVD-RW, network
<b>Network:</b>	Ethernet RJ-45 connector, 10/100Mbps, supports DHCP, DDNS
<b>Remote Operation:</b>	Monitor, Playback, Recording, System Setup, Dome Camera Control, Archiving
<b>Password Control:</b>	2 Level, Administrator / User
<b>Dimensions:</b>	362mm(W)* 350mm(D)* 90mm(H)
<b>Unit Weight:</b>	7 kg (15 lbs.)
<b>Operation Temperature:</b>	-5°C - 40°C (23°F - 104°F)
<b>Relative Humidity:</b>	10% - 90% Non - condensing