

## 8 Camera H.264 240fps Triplex Embedded DVR with USB backup

Model: DVRMINIH8



### Features

- 8 Channel Input
- Triplex (Recording, Playback, Network all at the same time)
- H.264 Compression
- Remote Viewing
- Real Time Display
- Up to 240fps Recording Speed
- Archiving via simple "1-touch" USB operation
- Stable Operation System (Embedded Linux)
- Firmware Upgradeable
- Scheduled Recording
- Password Protection
- IE Web Server and Remote Client
- PTZ Control via RS-485 (Pelco D, Pelco P)
- Camera Installation Plug & Play
- Automatic Camera Detection
- Supports Covert Camera Operation
- Supports Pre-Alarm Recording
- IR Remote Control Included
- Full Mouse Control
- Hard drive purchased separately

### Specifications

<b>Camera Inputs:</b>	8
<b>Image Compression:</b>	H.264
<b>Operating System:</b>	Embedded Linux
<b>Operation:</b>	Triplex(Playback / Record / Network View)
<b>Video Input:</b>	BNC x 8, 1.0Vp-p, 75 ohm
<b>Video Output:</b>	BNC to main monitor
<b>Video Output:</b>	VGA 800 x 600, 1024 x 768, 1280 x 1024 pixels
<b>Audio Inputs:</b>	8
<b>Audio Outputs:</b>	2
<b>Hard Drive:</b>	purchased separately, 2 HD Maximum (up to 2 Terabyte)

<b>Display:</b>	30 fps per channel (@720 x 480)
<b>Recording Rate:</b>	240 fps (@360 x 240), 120 fps (@720 x 240), 60 fps (@720 x 480)
<b>Recording Qualities:</b>	8 Preset Levels
<b>Recording:</b>	Schedule, Alarm, Motion Detection
<b>Search:</b>	Time, Date, Event
<b>Playback Speeds:</b>	1X, 2X, ...32X
<b>Alarm Inputs:</b>	8 D-Sub
<b>Alarm Outputs:</b>	1 relay output D-Sub
<b>Pre-Alarm operation:</b>	Yes
<b>PTZ Control</b>	RS-485 interface
<b>Archiving</b>	USB 2.0, network
<b>Network:</b>	Ethernet RJ-45 connector, 10/100 mbps, supports DHCP
<b>Remote Operation:</b>	Monitor, Playback, Recording, System Setup, Archiving
<b>Password Control:</b>	2 Level, Administrator / User
<b>Dimensions:</b>	9in(W) * 13in(D) * 2in(H)
<b>Unit Weight:</b>	8 lbs
<b>Operation Temperature:</b>	-5°C - 40°C (23°F - 104°F)
<b>Relative Humidity:</b>	10% - 90% Non - condensing