

This camera is a network-based digital surveillance device with a built-in web server for the purpose of remote monitoring and recording. It supports TCP/IP networking for live video transmission in the format of MPEG4 or MJPEG. You can easily operate the camera via the web browser or you can use the supplied video software for viewing and recording. Video surveillance over IP network infrastructure is available and easy from anywhere, anytime!

Model: IP101

Note: The IP01 and IP02IR cameras are compatible with each other using the provided Web Management Software (you can control up to 16 IP01 or IP02IR network cameras simultaneously). However, these IP cameras are not compatible with the VR Series software. If you are using the VR Series software then you have to use one of the VR Series IP Cameras or Servers. Please feel free to call our office for more information.

Product Includes:

- IP Camera
- Wall bracket
- Power Supply
- Central Management System (CMS) software
- Documentation
- Technical Support

Features:

- Complete IP surveillance system
- Low-latency video streaming for sharp and clear images
- Real Time Video Capture
- Remote Control
- Motion detection
- Indoor Use
- Ceiling or Wall Mount

Minimum Web Browsing Requirements:

- Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD
- 256 MB RAM
- AGP graphics card, Direct Draw, 32MB RAM

- Windows XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later
- Internet Explorer 6.x or later

Specifications	
Lan Port:	Yes
Lan Speed:	10/100 Based-T Ethernet
Supported Protocols:	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
Frame Rate:	30 fps
Number of Online Users:	10
Security:	Multiple user access levels with password
Web Management	YES (Control up to 16 IP01 or IP02IR network
Software:	cameras simultaneously)
Video Compression:	MPEG4 / MJPEG
Video Remote Control: Yes	
Video Adjustment:	Brightness, Contrast, Saturation and Hue
Image Sensor:	1/3.6" image sensor
Pixels:	738(H) x 480(V)
Lens:	3.6mm F2.0
Shutter Speed:	1/60 to 1/100,000 sec.
Min Illumination:	1.0 Lux
Video Output:	1.0 Vp-p. 75 ohms
BLC:	Auto
White Balance:	ATW
Power:	DC12V, 0.5A
Operating Temperature:	0~40°C (32° ~ 104°F)
Humidity:	85%
Dimensions (mm):	152.5(L) x 115.2(W) x 40.2(H)
Dimensions (inch):	6.00" x 4.54" x 1.58"
Weight:	812g (1.8 lbs) including mounting bracket and power supply