



The camera has a built-in web server that can be used to view and administrate the camera. In addition, the camera comes with our exclusive 16 channel VR Series Virtual DVR Client software. The Virtual Client will allow you to view and record the camera over the network, and to combine the camera with other VR Series components to create a complete enterprise-wide security solution.

Note:

This versatile camera includes both digital and analog output connections (so it can be hooked up to an analog or a digital network). The pigtail off the back of camera is about 2 ft long. This way the camera can be installed outside but the cable connection be made inside a building or weatherproof box.

Product Includes

- Infrared IP Camera 540 line resolution
- Power Supply
- Wall Bracket
- Built in IE Web Server
- VR Series 16 Channel Virtual Client software
- Manual
- Technical Support

Specifications

- H.264 Video Compression
- 540 line resolution
- 1/3" Sony Super HAD CCD
- 36 LED Infrared
- IR Range 75 ft.
- 6mm Lens
- 4CIF/DCIF/2CIF/CIF/QCIF real time compression
- Pixels 768×494
- Frame rate 1/16 to 30 FPS
- Transmission 32kbps--2Mbps (Self defined)
- Audio Output 1 Channel RCA
- Backlight Compensation
- SN Ratio: > 50dB (AGC off)
- Power: 12VDC 800ma
- RJ45 10M/100M

