



We now offer this awesome high quality vandal proof mini speed dome. This unit is about half the size of a conventional speed dome so it looks great indoors or out. On the ceiling it can be mounted flush or recessed into the ceiling. It has an optional wall bracket to allow wall mount. This unit will pan, tilt, or zoom up to 100X (total zoom = optical zoom X digital zoom). Great choice with the Optiview DVRs.

Notes:

1. To use a PTZ camera on our PC-Based DVRs, you must have an RS485 Converter.
2. Color shown here (with wall mount) is more indicative of cameras true color (off white).

**Mini PTZ with Optional Wall Mount****Product Includes**

- Ceiling bracket
- Power supply
- Installation / Instruction Manual
- Wall bracket is optional

Features

- 10X Digital Zoom
- 10X Optical Zoom
- Vandal Proof Dome
- Indoor / Outdoor
- Day / Night
- 360 Continuous Pan
- Small Footprint

Specifications

Image sensor:	1/4" Super HAD CCD
Horizontal Resolution:	500 TV Line
Pixels:	768 x 494
Min Illumination:	0.7 Lux (Day/Color), 0.02 Lux (Night/B&W)
Power Supply:	12 VDC 750 mA
Power Consumption:	9W Max
Dome:	Die-cast anti-vandal dome cover
Dimensions:	158.8 (D) x 163mm(H)
Weight:	1.5 kgs (approx 3.5 lbs)
Interface:	RS485
Focus:	Auto
Lens:	Auto
White Balance:	Auto/Manual
BLC:	On/Off
Flickerless:	On/Off
Auto Flip:	On/Off
Lens:	10X Optical & Digital Zoom, 3.8~38mm
Motor Type:	Stepper Motor
Micro Steps:	1/4 Step
Presets:	165 Preset positions
Group Tour:	8 Programmable Group Tours(Each one consisting of up to 60 preset steps)
Privacy Zone:	4 Privacy zones
Password Protection:	Yes
Alarm Input:	4 alarms Off/NC/NO (with various programmable states)
Alarm Actions:	Activate preset, Group scanning or Patterns
Pan Angle:	360° continuous pan rotation
Pan Speed:	150 degrees /s manual, 200 degrees /s preset
Operating Temp w/o heater:	0°C ~ 50°C
S/N Ratio:	> 50db