



Optiview's newest IP server allows real time streaming video via high speed network from camera to our enterprise VR series network server client allowing onsite recording and playback. Or you may view it via IE from any network connection.

### Features

- Embedded OS
- Embedded MCU
- High performance DSP hardware compression
- H.264 video compression algorithm and each channel can be real time 30FPS
- Motion detection
- Configurable OSD & LOGO
- Variable bit rate or variable frame rate
- Dual-stream and the sub stream can support CIF/QCIF compression resolution
- TCP, UTP, RTP, Multicast, DHCP, etc
- Remote parameters setup
- Remote upgradeable firmware
- Remote control PTZ
- Supports Internet Explore viewing
- Remote alarm information
- Each channel can support CIF compression resolution or 4CIF if less channels used.

### Specifications

TV System: NTSC

|                    |                      |
|--------------------|----------------------|
| <b>Dimensions:</b> | 198mm X 123mm X 39mm |
| <b>Resolution:</b> | 704 X 480(4CIF)      |
| <b>DCIF:</b>       | 528 X 320            |
| <b>2CIF:</b>       | 704 X 240            |
| <b>CIF:</b>        | 352 X 240            |
| <b>QCIF:</b>       | 176 X 120            |
| <b>Video:</b>      | 4 input              |
| <b>Audio:</b>      | 4 input              |